

## DUKKVALITET JP904FRL

Vår starkaste duk

## CANVAS QUALITY JP904FRL

Our strongest canvas

Flam skyddad	-	Flame retardancy
Lackad	-	Lacquered
Stark	-	Strong
Färg	-	Colour
Kvalitet	-	Quality
Tålig	-	Enduring
Långlivad	-	Long life



### Specifikation JP904FRL

Armeringsväv:	Polyester	
Garntjocklek:	Varp	1100 Dtex
	Väft	1100 Dtex
Konstruktion:	Panama 2/2	
Trådantal:	Varp	12 st/cm
	Väft	13 st/cm
Totalvikt:	900 g/m <sup>2</sup>	
Draghållfasthet:	Varp	4000 N/5 cm
EN-ISO 1421	Väft	4000 N/5 cm
Draghållfasthet över svets:	3800 N/5 cm	
Rivhållfasthet:	Varp	600 N
DIN 53356	Väft	600 N
Köldtålighet:	-30° C	
Värmebeständighet:	+70° C	
Flamskydd:	EN13501-1 B-s1,d0	
Miljöpåverkan:	Motstår rötsvampar, humussyra, dieselgaser, nitrösa gaser samt UV-ljus.	

### Specification JP904FRL

Reinforcing fabric:	Polyester	
Yarn density:	Warp	1100 Dtex
	Weft	1100 Dtex
Construction:	Panama 2/2	
Number of thread:	Warp	12 per cm
	Weft	13 per cm
Total weight:	900 g/m <sup>2</sup>	
Tensile strength:	Warp	4000 N/5 cm
EN-ISO 1421	Weft	4000 N/5 cm
Tensile strength over welding:	3800 N/5 cm	
Tear strength:	Warp	600 N
DIN 53356	Weft	600 N
Cold resistant:	-30° C	
Heat resistant:	+70° C	
Flame retardancy:	EN13501-1 B-s1,d0	
Environmental:	Withstands rot fungus, humic acid, dieselgas, nitrate gas and UV-light.	