

DUKKVALITET JP904FRL

Vår starkaste duk

CANVAS QUALITY JP904FRL

Our strongest canvas

Flam skyddad	-	Flame retardancy
Lackad	-	Lacquered
Stark	-	Strong
Färg	-	Colour
Kvalitet	-	Quality
Tålig	-	Enduring
Långlivad	-	Long life



Specifikation JP904FRL

Armeringsväv:	Polyester	
Garntjocklek:	Varp 1100 Dtex	Vävt 1100 Dtex
Konstruktion:	Panama 2/2	
Trådantal:	Varp 12 st/cm	Vävt 13 st/cm
Totalvikt:	900 g/m ²	
Draghållfasthet:	Varp 4000 N/5 cm	Vävt 4000 N/5 cm
EN-ISO 1421	Vävt 4000 N/5 cm	
Draghållfasthet över svets:	3800 N/5 cm	
Rivhållfasthet:	Varp 600 N	Vävt 600 N
DIN 53356	Vävt 600 N	
Köldtålighet:	-30° C	
Värmebeständighet:	+70° C	
Flamskydd:	EN13501-1 B-s1,d0	
Miljöpåverkan:	Motstår rötsvampar, humussyra, diesel gaser, nitrösa gaser samt UV-ljus.	

Specification JP904FRL

Reinforcing fabric:	Polyester	
Yarn density:	Warp 1100 Dtex	Weft 1100 Dtex
Construction:	Panama 2/2	
Number of thread:	Warp 12 per cm	Weft 13 per cm
Total weight:	900 g/m ²	
Tensile strength:	Warp 4000 N/5 cm	Weft 4000 N/5 cm
EN-ISO 1421	Weft 4000 N/5 cm	
Tensile strength over welding:	3800 N/5 cm	
Tear strength:	Warp 600 N	Weft 600 N
DIN 53356	Weft 600 N	
Cold resistant:	-30° C	
Heat resistant:	+70° C	
Flame retardancy:	EN13501-1 B-s1,d0	
Environmental:	Withstands rot fungus, humic acid, dieselgas, nitrate gas and UV-light.	