

DUKKVALITET JP712FRL

Special för särskilda behov

CANVAS QUALITY JP712FRL

Special for particular needs

Stark	-	Strong
Lackad	-	Lacquered
Färg	-	Colour
Kvalitet	-	Quality
Tålig	-	Enduring
Långlivad	-	Long life
Flamskydd	-	Flame retardancy



Specifikation JP712FRL

Armeringsväv:	Polyester	
Garntjocklek:	Varp	1100 Dtex
	Vävt	1100 Dtex
Konstruktion:	Tvåskaft	
Tråddantal:	Varp	9 st/cm
	Vävt	9 st/cm
Totalvikt:	730 g/m ²	
Draghållfasthet:	Varp	3000 N/5 cm
EN-ISO 1421	Vävt	2800 N/5 cm
Draghållfasthet över svets:	2800 N/5 cm	
Rivhållfasthet:	Varp	300 N
DIN 53356	Vävt	300 N
Köldtåligghet:	-30° C	
Värmebeständighet:	+70° C	
Flamskydd:	EN13501-1 B-s2,d0	
Miljöpåverkan:	Motstår rötsvampar, humussyra, dieselgaser, nitrösa gaser samt UV-ljus.	

Specification JP712FRL

Reinforcing fabric:	Polyester	
Yarn density:	Warp	1100 Dtex
	Weft	1100 Dtex
Construction:	Plain weave	
Number of thread:	Warp	9 per cm
	Weft	9 per cm
Total weight:	730 g/m ²	
Tensile strength:	Warp	3000 N/5 cm
EN-ISO 1421	Weft	2800 N/5 cm
Tensile strength over welding:	2800 N/5 cm	
Tear strength:	Warp	300 N
DIN 53356	Weft	300 N
Cold resistance:	-30° C	
Heat resistance:	+70° C	
Flame retardancy:	EN13501-1 B-s2,d0	
Environmental:	Withstands rot fungus, humic acid, dieselgas, nitrate gas and UV-light.	