

## DUKKVALITET JP703FR

Åtta färger att välja emellan

## CANVAS QUALITY JP703FR

Eight colours to choose

Flam skyddad	-	Flame retardancy
Stark	-	Strong
Färg	-	Colour
Kvalitet	-	Quality
Tålig	-	Enduring
Långlivad	-	Long life



### Specifikation JP703FR

Armeringsväv:	Polyester
Garntjocklek:	Varp 1430 Dtex Vävt 2 x 1100 Dtex
Konstruktion:	Halv panama
Tråddantal:	Varp 8 st/cm Vävt 8 st/cm
Totalvikt:	680 g/m <sup>2</sup>
Draghållfasthet:	Varp 2600 N/5 cm EN-ISO 1421 Vävt 2700 N/5 cm
Draghållfasthet över svets:	2200 N/5 cm
Rivhållfasthet:	Varp 450 N DIN 53356 Vävt 550 N
Köldtålighet:	-30° C
Värmebeständighet:	+70° C
Flamskydd:	EN13501-1 B-s1,d0
Miljöpåverkan:	Motstår rötsvampar, humussyra, dieselgaser, nitrösa gaser samt UV-ljus.

### Specification JP703FR

Reinforcing fabric:	Polyester
Yarn density:	Warp 1430 Dtex Weft 2 x 1100 Dtex
Construction:	Half panama
Number of thread:	Warp 8 per cm Weft 8 per cm
Total weight:	680 g/m <sup>2</sup>
Tensile strength:	Warp 2600 N/5 cm EN-ISO 1421 Weft 2700 N/5 cm
Tensile strength over welding:	2200 N/5 cm
Tear strength:	Warp 450 N DIN 53356 Weft 550 N
Cold resistance:	-30° C
Heat resistance:	+70° C
Flame retardancy:	EN13501-1 B-s1,d0
Environmental:	Withstands rotfungus, humic acid, dieselgas, nitrate gas and UV-light.