

DUKKVALITET JP602FR

Två standardfärger att välja emellan

CANVAS QUALITY JP602FR

Two standard colours to choose

Flam skyddad	-	Flame retardancy
Stark	-	Strong
Färg	-	Colour
Kvalitet	-	Quality
Tålig	-	Enduring
Långlivad	-	Long life

Specifikation JP602FR

Armeringsväv:	Polyester
Garntjocklek:	Varp 1100 Dtex Väft 1100 Dtex
Konstruktion:	2-skaft
Trådantal:	Varp 4,7 st/cm Väft 4,7 st/cm
Totalvikt:	600 g/m ²
Draghållfasthet: EN-ISO 1421	Varp 1500 N/5 cm Väft 1500 N/5 cm
Draghållfasthet över svets:	1200 N/5 cm
Rivhållfasthet: DIN 53356	Varp 350 N Väft 350 N
Köldtålighet:	-30° C
Värmebeständighet:	+70° C
Flamskydd:	EN13501-1 B-s1,d0
Miljöpåverkan:	Motstår rötsvampar, humussyra, dieselgaser, nitrosa gaser samt UV-ljus.

Specification JP602FR

Reinforcing fabric:	Polyester
Yarn density:	Warp 1100 Dtex Weft 1100 Dtex
Construction:	Plain weave
Number of thread:	Warp 4,7 per cm Weft 4,7 per cm
Total weight:	600 g/m ²
Tensile strength: EN-ISO 1421	Warp 1500 N/5 cm Weft 1500 N/5 cm
Tensile strength over welding:	1200 N/5 cm
Tear strength: DIN 53356	Warp 350 N Weft 350 N
Cold resistant:	-30° C
Heat resistant:	+70° C
Flame retardancy:	EN13501-1 B-s1,d0
Environmental:	Withstands rot fungus, humic acid, dieselgas, nitrate gas and UV-light.